

PRESSURE TRANSDUCER

Information

Safely measure hydraulic pressures, away from the line of fire with SafeGauge's Wireless Pressure Transducers.

Using the SafeGauge Multi-Tool Pro, live data from 12 sensors can safely be monitored from up to 100m (328ft) away. The rugged case includes inbuilt charging and everything needed to make rapid measurements safely.

Unit of measurement can be changed in the settings of the SafeGauge Multi-Tool Pro.

Features

1. Pressure Transducer
2. Wireless MultiTool Pro
3. Universal Power Supply



Safegauge 12 Channel PT Kit
PT-12

Quick Setup

1. Remove the Pressure Transducer from the kit and unplug the charging cable. The status LED will begin flashing **blue**.



2. Turn on the Multi-Tool Pro by pressing the power button on the right-hand side.



3. Press the channel programmed for the sensor's serial number. The channel status will change from Scanning to Connected, and the Pressure Transducer status LED will start flashing green. Set the test point "Nickname" by pressing the "Edit" button on the right of the desired channel.



4. Attach the transducer to the desired test point using hydraulic couplings.



5. The test page will show the accurate Pressure Transducer reading and min & max pressures.



6. "Function" then "Difference" can be selected to show the difference in pressure between any two sensors.



If you have any questions or concerns with the usability of SafeGauge products, please don't hesitate to reach out to us on 1300 222 392. We appreciate your feedback to help improve our products and our customers satisfaction and safety when completing live work.